## NSN 5910-01-336-9474

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-336-9474

**Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 3.660 inches **Body Width:** 1.970 inches **Body Height:** 3.500 inches **Center To Center Distance Between Terminals Parallel To Length:** 1.380 inches **Terminal Diameter:** 0.250 inches **Terminal Height From Body:** 1.120 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 2 threaded mounting studs **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 100.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 70.0 degrees celsius Thread Size: 0.250 inches Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 250.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -3.0/+3.0 single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

100000.0 megohms

## NSN 5910-01-336-9474

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Dissipation Factor At Reference Tempurature In Percent:
0.600
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester
Terminal Type And Quantity:
2 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0