NSN 5910-01-336-9839

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-336-9839

view Online at https://aerobasegroup.com/nsn/5910-01-556-9659
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
4.0 millimeters
Body Length:
10.5 millimeters
Body Width:
8.0 millimeters
Body Height:
4.0 millimeters
Center To Center Distance Between Terminals Parallel To Length:
7.5 millimeters
Terminal Diameter:
0.7 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
15000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-01-336-9839

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0