NSN 5910-01-337-0284

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-337-0284

view On	ille at https://aerobasegroup.com/hsh/5910-01-337-0264
Body St	yle:
W/o mtg	facilities terminal (s) on one surface
Reliabili	ty Indicator:
Not esta	blished
Termina	ıl Length:
4.0 millin	neters
Body Le	ength:
10.5 mill	imeters
Body W	idth:
8.0 millir	neters
Body He	eight:
4.0 millin	neters
Center 7	To Center Distance Between Terminals Parallel To Length:
7.5 millin	neters
Termina	ll Diameter:
0.7 millin	neters
Schema	tic Diagram Designator:
No comr	non or grounded electrode (s)
Capacit	ance Value Per Section:
0.022 mi	crofarads single section
Nondera	ated Operating Temp:
Between	-55.0 degrees celsius and 85.0 degrees celsius
Tempur	ature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 singl	e section
Nondera	ated Continuous Voltage Rating And Type Per Section:
250.0 do	single section
Toleran	ce Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-100.0/+	100.0 single section
	ce Range Per Section:
	.00 percent single section
Case Ma	aterial:
Plastic	
	on Resistance At Reference Temp:
	megohms
-	tion Factor At Reference Tempurature In Percent:
0.300	
	Il Surface Treatment:
Solder	
	ic Material:
Plastic p	
ı ermına	Il Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-337-0284

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0