Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



NSN 5910-01-338-8173 View Online at https://aerobasegroup.com/nsn/5910-01-338-8173 **Body Style:** W/o mtg facilities terminal (s) on one surface Reliability Indicator: Not established **Terminal Length:** 4.0 millimeters **Body Length:** 10.5 millimeters **Body Width:** 7.5 millimeters **Body Height:** 2.5 millimeters Center To Center Distance Between Terminals Parallel To Length:

Between 7.1 millimeters and 7.9 millimeters

**Terminal Diameter:** 

0.7 millimeters

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

0.056 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 100.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

**Tolerance Range Per Section:** 

-5.00/+5.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

50000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic polyester

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-01-338-8173

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0