NSN 5910-01-339-0234

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-0234

Body Style:						
W/o mtg facilities, axial terminals						
Reliability Indicator:						
Not established						
Terminal Length:						
1.750 inches						
Body Diameter:						
0.348 inches						
Body Length:						
0.750 inches						
Terminal Diameter:						
0.032 inches						
Schematic Diagram Designator:						
No common or grounded electrode (s)						
End Application:						
Tactical air operations module an/tyq-2 (v) 1						
Insulation Resistance At Maximum Operating Temp:						
10000.0 megohm-microfarads						
Capacitance Value Per Section:						
0.100 microfarads single section						
Nonderated Operating Temp:						
Between -55.0 degrees celsius and 85.0 degrees celsius						
Nonderated Continuous Voltage Rating And Type Per Section:						
400.0 dc single section						
Tolerance Range Per Section:						
-5.00/+5.00 percent single section						
Case Material:						
Plastic						
Insulation Resistance At Reference Temp:						
200000.0 megohm-microfarads						
Dissipation Factor At Reference Tempurature In Percent:						
0.100						
Terminal Surface Treatment:						
Solder						
Dielectric Material:						
Plastic polypropylene						
Terminal Type And Quantity:						
2 uninsulated wire lead						
Shelf Life:						
Shelf Life: N/a						

--

NSN 5910-01-339-0234

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	\sim	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ıu		

No

Fiig:

A010b0