NSN 5910-01-339-2064

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-2064

Body Style: W/thd bushing mtg, terminals on opposite ends Reliability Indicator: Not established **Terminal Length:** 0.750 inches **Body Diameter:** 0.250 inches **Body Length:** 0.310 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** Feedthrough **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 1 threaded bushing **Capacitance Value Per Section:** 1500.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.164 inches Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.150 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:**

2 uninsulated wire lead

NSN 5910-01-339-2064

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0