## NSN 5910-01-339-2066

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-2066

**Body Style:** 

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

**Terminal Length:** 

Between 4.0 millimeters and 5.0 millimeters

**Body Diameter:** 

40.0 millimeters

**Body Length:** 

55.0 millimeters

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Anode Type:** 

Plain foil

**Impedance At Minimum Operating Tempurature In Ohms:** 

27 N

**Electrical Polarization:** 

Polarized

**End Application:** 

Tactical air operations module an/tyq-2 (v) 1

**Features Provided:** 

Mounting hardware

**Capacitance Value Per Section:** 

10000.000 microfarads single section

**Nonderated Operating Temp:** 

Between -40.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:** 

4.9 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

40.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+30.00 percent single section

**Case Material:** 

Metal

**Capacitive Electrode Material:** 

Aluminum

**Dissipation Factor At Reference Tempurature In Percent:** 

0.190

**Equivalent Series Resistance At Reference Tempurature In Ohms:** 

35.00

Dc Leakage At Reference Temp:

2.400 milliamperes

## NSN 5910-01-339-2066 Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
3 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0