## NSN 5910-01-339-3953

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-3953 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.625 inches **Body Length:** 0.295 inches **Body Width:** 0.235 inches **Body Height:** 0.108 inches Center To Center Distance Between Terminals Parallel To Length: 0.200 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 0.0015 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Plastic **Insulation Resistance At Reference Temp:** 500000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.300

**Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polycarbonate **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5910-01-339-3953

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	<b>2</b> †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0