NSN 5910-01-339-6754

Body Style:

Rotary

2 ribbon

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-6754

Terminal Length: 0.172 inches **Body Diameter:** Between 0.116 inches and 0.136 inches **Body Height:** 0.086 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -750.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -350.0/+350.0 single section **Quality Factor At 25 Deg Celsius:** 100.0 **Dissipation Factor At 25 Deg Celsius In Percent: Fragility Factor:** Moderately delicate **Terminal Width:** Between 0.026 inches and 0.036 inches **Terminal Thickness:** Between 0.004 inches and 0.006 inches **Inclosure Type:** Encased **Adjustment Device Torque:** Between 0.200 inch-ounces and 1.500 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +5.0/+35.0 single section Nonderated Voltage Rating And Type: 25.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw Material: Ceramic capacitive electrode **Terminal Type And Quantity:**

NSN 5910-01-339-6754

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf Li	fe:
----------	-----

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0