NSN 5910-01-339-9055

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-339-9055

| Body Style: |
|---|
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 6.0 millimeters |
| Body Length: |
| 10.5 millimeters |
| Body Width: |
| 8.0 millimeters |
| Body Height: |
| 4.0 millimeters |
| Center To Center Distance Between Terminals Parallel To Length: |
| 7.6 millimeters |
| Terminal Diameter: |
| 0.6 millimeters |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.047 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+20.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 30000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.030 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polyester |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5910-01-339-9055

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • - | | | | |
|---|----|----|-----|-----|-------------|-----|----|
| 1 | em | | ゖっ | riz | 2 †1 | n | |
| _ | | | ıιa | 114 | au | VII | ١. |

No

Fiig:

A010b0