## NSN 5910-01-340-0594

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-340-0594

**Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** Between 0.155 inches and 0.219 inches **Body Diameter:** 0.300 inches **Body Length:** 0.470 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.100 inches **Terminal Diameter:** Between 0.018 inches and 0.022 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **End Application:** 6625-01-224-4440 network analyze **Capacitance Value Per Section:** 22.000 microfarads single section **Nonderated Operating Temp:** 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.000 Dc Leakage At Reference Temp: 4.400 microamperes **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-340-0594

Electrolytic Fixed Capacitor - Page 2 of 2



|  |  | fe: |
|--|--|-----|
|  |  |     |
|  |  |     |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0