## NSN 5910-01-340-1124

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-340-1124 **Body Style: Dual inline Reliability Indicator:** Not established **Terminal Length:** Between 0.120 inches and 0.176 inches **Body Length:** 0.092 inches **Body Width:** 0.260 inches **Body Height:** 0.128 inches **Center To Center Distance Between Terminals Parallel To Width:** Between 0.290 inches and 0.360 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Burn in **Insulation Resistance At Maximum Operating Temp:** 10000.0 megohms **Capacitance Value Per Section:** 220.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -30.0/+30.0 single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Plastic Insulation Resistance At Reference Temp: 100000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.150 **Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 printed circuit

## NSN 5910-01-340-1124

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



elf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0