## NSN 5910-01-340-1140

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-340-1140 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 5.0 millimeters **Body Diameter:** 4.5 millimeters **Body Length:** 12.0 millimeters **Terminal Diameter:** 0.6 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Etched foil **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 10.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+100.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 35.00 Dc Leakage At Reference Temp: 19.000 milliamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** 

**Plastic** 

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-340-1140

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0