Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-340-1152

### Body Style:

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

## **Terminal Length:**

0.150 inches

#### **Body Length:**

0.394 inches

#### **Body Width:**

0.335 inches

#### **Body Height:**

#### 0.118 inches

#### Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

#### **Terminal Diameter:**

0.024 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

0.022 microfarads single section

### Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Plastic

#### Insulation Resistance At Reference Temp:

7500.0 megohm-microfarads

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.015

## **Terminal Surface Treatment:**

Solder

## Dielectric Material:

Plastic polyester

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0