## NSN 5910-01-340-9866



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-340-9866 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 25.0 millimeters **Body Diameter:** 5.0 millimeters **Body Length:** 11.0 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 2.0 millimeters **Terminal Diameter:** 0.032 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **Features Provided:** Burn in **Capacitance Value Per Section:** 2.200 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum Dc Leakage At Reference Temp: 2.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic** 

Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-340-9866

Electrolytic Fixed Capacitor - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

10933-1-001-0302-0031 manufacturers specification control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0