Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-341-0866

Body Style:

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.236 inches

Body Length:

0.985 inches

Body Width:

0.729 inches

Body Height:

0.335 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.871 inches and 0.903 inches

Terminal Diameter:

Between 0.029 inches and 0.033 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

1.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

400.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

160.0 ac-rms single section and 250.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-200.0/+200.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

15000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.800

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polyester

Terminal Type And Quantity:

2 uninsulated wire lead

AeroBase Group

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0