NSN 5910-01-341-5613

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-341-5613
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
5.0 millimeters
Body Length:
7.2 millimeters
Body Width:
6.5 millimeters
Body Height:
2.5 millimeters
Center To Center Distance Between Terminals Parallel To Length:
Between 4.6 millimeters and 5.4 millimeters
Terminal Diameter:
0.5 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
Tactical air operations module an/tyq-2 (v) 1
Capacitance Value Per Section:
0.220 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
400.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-200.0/+200.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
50000.0 megohms
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead

Shelf Life: N/a

NSN 5910-01-341-5613

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A010b0