Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-342-1179

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

# Body Length:

0.190 inches

**Body Width:** 

0.190 inches

**Body Height:** 

0.090 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

W/formed leads

#### Capacitance Value Per Section:

0.470 nanofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### Tolerance Range Per Section:

-10.00/+10.00 percent single section

### **Test Data Document:**

81349-mil-c-39014e specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 standoff, wire lead

#### **Specification Data:**

81349-mil-c-39014/1e government specification

### Shelf Life:

N/a

# Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A010b0