

View Online at <https://aerobasegroup.com/nsn/5910-01-342-4487>

Body Style:

Chip type

Reliability Indicator:

Not established

Terminal Length:

Between 0.010 inches and 0.040 inches

Body Length:

Between 0.210 inches and 0.245 inches

Body Width:

Between 0.235 inches and 0.270 inches

Body Height:

0.080 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

An/uyk-4 (v) computer. Forrestal class cv, ticonderoga class cg (47), nimitz class cvn, wasp class lhd, oliver perry class ffg, kidd class ddg, arleig burke class ddg, spruance class dd (963) .

Capacitance Value Per Section:

1000000.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Ceramic

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 bonding pad

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0