## NSN 5910-01-345-4157

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-345-4157

**Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.380 inches **Body Diameter:** 0.315 inches **Body Length:** 0.787 inches **Terminal Diameter:** 0.024 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Electrical Polarization:** Polarized **End Application:** 5895-01-163-1168 frequency contr **Capacitance Value Per Section:** 470.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 100.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 16.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.47 Dc Leakage At Reference Temp: 46.000 microamperes **Terminal Surface Treatment:** 

Solder

## NSN 5910-01-345-4157

Electrolytic Fixed Capacitor - Page 2 of 2



Case insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0