

View Online at https://aerobasegroup.com/nsn/5910-01-346-7519

| Body Style: |
|--|
| Chip type |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.010 inches and 0.030 inches |
| Body Length: |
| Between 0.165 inches and 0.195 inches |
| Body Width: |
| Between 0.065 inches and 0.095 inches |
| Body Height: |
| Between 0.020 inches and 0.080 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Insulation Resistance At Maximum Operating Temp: |
| 1000.0 megohms |
| Capacitance Value Per Section: |
| 470.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -5.00/+5.00 percent single section |
| Case Material: |
| Ceramic |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.150 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |



Demilitarization:

No

Fiig:

A010b0