

View Online at <https://aerobasegroup.com/nsn/5910-01-346-7524>

Body Style:

Dual inline

Reliability Indicator:

Not established

Terminal Length:

0.120 inches

Body Length:

0.200 inches

Body Width:

Between 0.290 inches and 0.310 inches

Body Height:

0.180 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.090 inches and 0.110 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.325 inches and 0.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Solid

Electrical Polarization:

Polarized

Section Quantity:

2

Capacitance Value Per Section:

33.000 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc all sections

Tolerance Range Per Section:

-10.00/+10.00 percent all sections

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-49137 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

4 printed circuit

Specification Data:

81349-mil-c-49137/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0