## NSN 5910-01-347-1549

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-347-1549

| Body Style:   |
|---|
| W/o mtg facilities terminal (s) on one surface                        |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 1.250 inches  |
| Body Length:  |
| 0.770 inches  |
| Body Width:   |
| 0.720 inches  |
| Body Height:  |
| 0.270 inches  |
| Center To Center Distance Between Terminals Parallel To Length:       |
| Between 0.645 inches and 0.705 inches                                 |
| Terminal Diameter:  |
| 0.025 inches  |
| Schematic Diagram Designator:   |
| No common or grounded electrode (s)                                   |
| Insulation Resistance At Maximum Operating Temp:                      |
| 1000.0 megohms  |
| Capacitance Value Per Section:  |
| 330000.000 picofarads single section                                  |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: |
| -15.0/+15.0 without voltage applied single section                    |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 125.0 degrees celsius               |
| Nonderated Continuous Voltage Rating And Type Per Section:            |
| 1500.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+10.00 percent single section                                  |
| Case Material:  |
| Plastic   |
| Insulation Resistance At Reference Temp:                              |
| 100000.0 megohms  |
| Dissipation Factor At Reference Tempurature In Percent:               |
| 2.500   |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 uninsulated wire lead   |
| Shelf Life:   |

N/a

## NSN 5910-01-347-1549

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0