

View Online at https://aerobasegroup.com/nsn/5910-01-347-8757

| View Online at https://aerobasegroup.com/nsn/5910-01-347-8757 |
|--|
| Body Style: |
| Chip type |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.095 inches and 0.125 inches |
| Body Length: |
| Between 0.095 inches and 0.125 inches |
| Body Width: |
| Between 0.095 inches and 0.125 inches |
| Body Height: |
| 0.100 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Features Provided: |
| Burn in |
| Capacitance Value Per Section: |
| 36.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 175.0 degrees celsius |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 90.0 single section |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 100.0 dc single section |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -30.0/+30.0 single section |
| Tolerance Range Per Section: |
| -2.00/+2.00 percent single section |
| Case Material: |
| Glass |
| Insulation Resistance At Reference Temp: |
| 100000.0 megohms |
| Terminal Surface Treatment: |
| Palladium and silver |
| Precious Material And Location: |
| Terminal surfaces palladium and terminal surfaces silver |
| Terminal Type And Quantity: |
| 2 bonding pad |
| Shelf Life: |
| N/a |
| Unit Of Measure: |



Demilitarization:

No

Fiig:

A010b0