

View Online at <https://aerobasegroup.com/nsn/5910-01-347-8763>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established

**Unable To Decode:**

Unable to decode and unable to decode

**Terminal Length:**

Between 0.110 inches and 0.120 inches

**Unable To Decode:**

Unable to decode and unable to decode

**Unable To Decode:**

Unable to decode and unable to decode

**Body Diameter:**

Between 0.123 inches and 0.133 inches

**Body Length:**

Between 0.105 inches and 0.115 inches

**Terminal Diameter:**

Between 0.029 inches and 0.031 inches

**Schematic Diagram Designator:**

Feedthrough

**Features Provided:**

Burn in and hermetically sealed case

**Capacitance Value Per Section:**

1000.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

150.0 dc single section

**Tolerance Range Per Section:**

-0.00/+100.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

500.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

5.000

**Terminal Surface Treatment:**

Gold

**Precious Material And Location:**

Terminal surfaces gold

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0