NSN 5910-01-348-7120

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-348-7120

view Offilite at https://defobasegroup.com/hist//00/10-01-040-7/120
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.157 inches and 0.236 inches
Body Length:
0.511 inches
Body Width:
0.177 inches
Body Height:
0.394 inches
Center To Center Distance Between Terminals Parallel To Length:
0.394 inches
Terminal Diameter:
0.032 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.068 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 100.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-4.0/+5.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
30000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.750
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polycarbonate
Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-348-7120

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0