## NSN 5910-01-349-3056

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-349-3056

<b>Body</b>	Stv	-ما
DUUV	OLV.	ıc.

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.185 inches and 0.235 inches

**Unable To Decode:** 

Unable to decode and unable to decode

**Unable To Decode:** 

Unable to decode and unable to decode

**Body Diameter:** 

Between 0.123 inches and 0.133 inches

**Body Length:** 

0.110 inches

**Terminal Diameter:** 

Between 0.027 inches and 0.033 inches

**Schematic Diagram Designator:** 

Feedthrough

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

10.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

**Tolerance Range Per Section:** 

-0.00/+100.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Terminal Surface Treatment:** 

Gold

**Precious Material And Location:** 

Terminal surfaces gold

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5910-01-349-3056

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0