NSN 5910-01-349-5164

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-349-5164

Body Style: W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.984 inches **Body Diameter:** 0.511 inches **Body Length:** 0.787 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.196 inches **Terminal Diameter:** 0.023 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 2.000 **Electrical Polarization:** Polarized **End Application:** 6625-01-288-6361 generator sweep **Capacitance Value Per Section:** 220.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** 7.000 **Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.36

Dc Leakage At Reference Temp:

2.000 microamperes

NSN 5910-01-349-5164

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0