NSN 5910-01-349-5436

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-349-5436

| view Offiline at https://aerobasegroup.com/nish/00/10-01-040-0400 |
|---|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.000 inches |
| Body Length: |
| 0.310 inches |
| Body Width: |
| 0.230 inches |
| Body Height: |
| 0.130 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| Between 0.175 inches and 0.225 inches |
| Terminal Diameter: |
| Between 0.015 inches and 0.017 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Anode Type: |
| Solid |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 33.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Dc Leakage At Maximum Operating Temp: |
| 30.0 microamperes |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 10.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Capacitive Electrode Material: |
| Tantalum |
| Dc Leakage At Reference Temp: |
| 3.000 microamperes |
| Terminal Surface Treatment: |
| Solder |

2 uninsulated wire lead

Terminal Type And Quantity:

NSN 5910-01-349-5436

Electrolytic Fixed Capacitor - Page 2 of 2



| | | | | - |
|-----|----|-----|-----|-----|
| C I | 20 | lŧ. | l i | fe: |
| J. | 16 | | _, | ıc. |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0