

View Online at <https://aerobasegroup.com/nsn/5910-01-351-4662>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.156 inches

Terminal Length:

0.080 inches

Body Length:

0.350 inches

Continuous Current Rating In Amps:

10.0

Terminal Diameter:

0.032 inches

Schematic Diagram Designator:

Feedthrough

End Application:

5895-01-299-3419 converter, signal

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

0.050 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100.0 megohms

Terminal Surface Treatment:

Solder

Precious Material And Location:

All metal parts silver

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0