NSN 5910-01-351-4662

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-351-4662 **Body Style:** W/thd mtg bushing, terminals on opposite ends **Reliability Indicator:** Not established Width Across Flats: 0.156 inches **Terminal Length:** 0.080 inches **Body Length:** 0.350 inches **Continuous Current Rating In Amps:** 10.0 **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Feedthrough **End Application:** 5895-01-299-3419 converter, signal **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 1 threaded bushing **Capacitance Value Per Section:** 0.050 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.112 inches Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 100.0 megohms **Terminal Surface Treatment:** Solder

Precious Material And Location:

All metal parts silver

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-351-4662

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0