

View Online at <https://aerobasegroup.com/nsn/5910-01-351-5532>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.235 inches and 0.265 inches

Body Diameter:

Between 0.985 inches and 1.015 inches

Body Length:

Between 2.127 inches and 2.177 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.285 inches and 0.315 inches

Terminal Diameter:

Between 0.037 inches and 0.043 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

0.13

Electrical Polarization:

Polarized

Capacitance Value Per Section:

100.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

474.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.78

Dc Leakage At Reference Temp:

79.000 microamperes

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

3 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0