## NSN 5910-01-352-3337

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-352-3337

·
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 0.750 inches and 1.250 inches
Body Length:
1.750 inches
Body Width:
0.950 inches
Body Height:
0.800 inches
Center To Center Distance Between Terminals Parallel To Length:
1.140 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 105.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-250.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
350.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
50000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.050
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polypropylene
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-352-3337

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0