

View Online at <https://aerobasegroup.com/nsn/5910-01-355-6957>

**Body Style:**

W/thd mtg hol (s)/stud(s) terminals on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

0.250 inches

**Body Length:**

4.450 inches

**Body Width:**

2.500 inches

**Body Height:**

2.250 inches

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.280 inches and 0.320 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.280 inches and 0.320 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 3.640 inches and 3.650 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.680 inches and 1.700 inches

**Internal Electrical Connection Type:**

Extended foil

**Mounting Facility Screw Thread Series Designator:**

Unf

**Mounting Facility Type And Quantity:**

4 threaded mounting studs

**Section Quantity:**

3

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

2.800 microfarads all sections

**Nonderated Operating Temp:**

Between -65.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.190 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

208.0 dc all sections

**Tolerance Range Per Section:**

-10.00 to 10.00 percent all sections

**Case Material:**

Metal

**Power Factor At Reference Temperature In Percent:**

2.000

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Paper or plastic

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0