

View Online at <https://aerobasegroup.com/nsn/5910-01-356-4113>

**Body Style:**

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:**

Not established

**Terminal Length:**

4.5 millimeters

**Body Length:**

8.0 millimeters

**Body Width:**

12.5 millimeters

**Body Height:**

6.0 millimeters

**Center To Center Distance Between Terminals Parallel To Length:**

5.0 millimeters

**Terminal Diameter:**

0.6 millimeters

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Solid

**Impedance At Minimum Operating Temperature In Ohms:**

0.7

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

47.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

6.3 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

0.160

**Equivalent Series Resistance At Reference Temperature In Ohms:**

6.40

**Dc Leakage At Reference Temp:**

7.400 microamperes

**Terminal Surface Treatment:**

Solder

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0