

View Online at <https://aerobasegroup.com/nsn/5910-01-356-8922>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Terminal Length:**

0.250 inches

**Body Diameter:**

3.000 inches

**Body Length:**

5.125 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Electrical Polarization:**

Polarized

**End Application:**

Fa9996, second generation vortac

**Capacitance Value Per Section:**

14000.000 microfarads single section

**Nonderated Operating Temp:**

Between -10.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

100.0 dc single section

**Tolerance Range Per Section:**

+0.00/+50.00 microfarads single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Special Features:**

1a1a3c1, ti 6820.2, fa 9996/1, vortac, vor/dme, vor equipment, sec 8, vol 8, pg 8-32

**Terminal Type And Quantity:**

3 standard tube base

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A010b0