NSN 5910-01-356-9249

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-356-9249

Rody	Style:
Douv	Style.

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 0.300 inches and 0.560 inches

Body Length:

0.150 inches

Body Width:

0.150 inches

Body Height:

0.100 inches

Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

Terminal Diameter:

0.016 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

5895-01-340-9279 base station, communication terminal

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

240.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.150

Terminal Surface Treatment:

Solder

NSN 5910-01-356-9249

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0