NSN 5910-01-357-3279

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.120 inches
Body Width:
0.100 inches
Body Height:
0.120 inches
Terminal Diameter:
0.016 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
20.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-1600.0 single section
No. 1 and 10 and a second Walkers Burger As LT as Base Conference
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
100.0 dc single section
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section:
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp:
100.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 300.000
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 300.000 Terminal Surface Treatment:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 300.000 Terminal Surface Treatment: Solder
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -15.0/+15.0 single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 100000.0 megohms Quality Factor At Reference Temp: 300.000 Terminal Surface Treatment: Solder Terminal Type And Quantity:

--

Unit Of Measure:

NSN 5910-01-357-3279

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0