NSN 5910-01-359-4066

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-359-4066 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.500 inches **Body Diameter:** 0.157 inches **Body Length:** 0.275 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.200 inches **Terminal Diameter:** 0.016 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 23.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1.500 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 4.000 Dc Leakage At Reference Temp: **Terminal Surface Treatment:**

1.000 microamperes Solder **Terminal Type And Quantity:** 2 uninsulated wire lead

NSN 5910-01-359-4066

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0