NSN 5910-01-359-5816

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-359-5816

view Online at https://aerobasegroup.com/nsn/os10-01-555-5610
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
1.625 inches
Body Diameter:
0.235 inches
Body Length:
0.469 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Insulation Resistance At Maximum Operating Temp:
7000.0 megohms
Capacitance Value Per Section:
0.022 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
500000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.300
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-55514 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:

Shelf Life:

2 uninsulated wire lead **Specification Data:**

81349-mil-c-55514/4 government specification

N/a

NSN 5910-01-359-5816

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	• -			
In	ıŧ	()t	Measure	•

--

Demilitarization:

No

Fiig:

A010b0