# NSN 5910-01-360-6092

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-360-6092

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

**Terminal Length:** 

1.250 inches

**Body Length:** 

Between 0.280 inches and 0.300 inches

**Body Width:** 

Between 0.280 inches and 0.300 inches

**Body Height:** 

Between 0.080 inches and 0.100 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.185 inches and 0.215 inches

**Terminal Diameter:** 

Between 0.023 inches and 0.029 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:** 

10000.0 megohms

**Capacitance Value Per Section:** 

2200.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.150

**Terminal Surface Treatment:** 

Solder

# NSN 5910-01-360-6092

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



#### **Test Data Document:**

81349-mil-c-20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

2 uninsulated wire lead

### **Specification Data:**

81349-mil-c-20/36 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0