## NSN 5910-01-360-8750



Air Dielectric Variable Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-360-8750 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.500 inches **Terminal Length:** 0.016 inches **Bushing Diameter:** 0.190 inches **Bushing Length:** 0.230 inches **Body Length:** 0.270 inches **Overall Diameter:** Between 0.215 inches and 0.235 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 7500.0 **Fragility Factor:** Moderately rugged **Terminal Thickness:** 0.010 inches **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type: Encased Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.400 inch-ounces and 4.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Mounting Facility Type And Quantity:** 

1 threaded bushing

Thready Qty Per Inch (tpi):

64

## NSN 5910-01-360-8750

Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Operating Temp:
Between -65.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.190 inches
Capacitance Range In Picofarads:
+0.8/+10.0 single section
Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Material:
Brass base
Terminal Type And Quantity:
1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0