## NSN 5910-01-361-2092



Ceramic Dielectric Fixed Capacitor - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5910-01-361-2092 **Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Established Reliability Failure Rate Level In Percent: 0.010 **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** W/formed leads **Capacitance Value Per Section:** 4.700 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -0.25/+0.25 percent single section **Test Data Document:** 81349-mil-c-20h specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead **Specification Data:** 81349-mil-c-20/35g government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A010b0