

View Online at https://aerobasegroup.com/nsn/5910-01-361-2093

### **Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.010

# Body Length:

0.190 inches

#### **Body Width:**

0.190 inches

**Body Height:** 

0.090 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

W/formed leads

#### **Capacitance Value Per Section:**

6.800 picofarads single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-0.25/+0.25 percent single section

### **Test Data Document:**

81349-mil-c-20h specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 uninsulated wire lead

### **Specification Data:**

81349-mil-c-20/35g government specification

#### Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A010b0