NSN 5910-01-364-2539

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-364-2539 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** Between 1.250 inches and 1.750 inches **Body Diameter:** 0.185 inches **Body Length:** 0.474 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 22.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 40.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Dissipation Factor At Reference Tempurature In Percent:** 6.000 Dc Leakage At Reference Temp: 4.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-364-2539

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0