NSN 5910-01-364-3599



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-364-3599 **Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 20.0 millimeters **Body Diameter:** 5.0 millimeters **Body Length:** 11.0 millimeters **Center To Center Distance Between Terminals Parallel To Diameter:** 2.0 millimeters **Terminal Diameter:** 0.5 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 60.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 4.700 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal

Tolerance Range Per Section:
-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:
0.100

Dc Leakage At Reference Temp:
3.000 microamperes

Terminal Surface Treatment:

Solder

Plastic

Case Insulation Material:

NSN 5910-01-364-3599

Electrolytic Fixed Capacitor - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0