## NSN 5910-01-364-4296

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-364-4296 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 millimeters **Body Length:** 0.150 millimeters **Body Width:** 0.100 millimeters **Body Height:** 0.150 millimeters **Center To Center Distance Between Terminals Parallel To Length:** 0.100 millimeters **Terminal Diameter:** 0.016 millimeters **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 6.800 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 120.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 100.0 dc single section **Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:** -60.0/+60.0 single section **Tolerance Range Per Section:** -0.500/+0.500 picofarads single section Case Material: Plastic **Terminal Surface Treatment:** Solder **Test Data Document:** 87990-755002a7705 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 uninsulated wire lead

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5910-01-364-4296

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0