NSN 5910-01-364-4689

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-364-4689

| view Offiline at https://aerobasegroup.com/his//05/10-01-304-4005 |
|---|
| Body Style: |
| W/o mtg facilities, terminals on opposite surfaces |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| Between 0.350 inches and 0.450 inches |
| Body Width: |
| Between 0.050 inches and 0.150 inches |
| Body Height: |
| Between 0.150 inches and 0.250 inches |
| Terminal Diameter: |
| 0.020 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 0.100 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 125.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -1.00/+1.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 25000.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: |
| 0.300 |
| Terminal Surface Treatment: |
| Solder |
| Dielectric Material: |
| Plastic polycarbonate |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-01-364-4689

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0