## NSN 5910-01-365-9920

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-365-9920

, 3,
Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.709 inches
Body Length:
0.295 inches
Body Width:
0.283 inches
Body Height:
0.103 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.169 inches and 0.231 inches
Terminal Diameter:
Between 0.018 inches and 0.027 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
End Application:
6625-01-285-9218 generator, signal
Capacitance Value Per Section:
0.022 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
400.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-200.0/+200.0 single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Plastic
Dissipation Factor At Reference Tempurature In Percent:
0.010
Terminal Surface Treatment:
Solder
Dielectric Material:
Plastic polyester
Terminal Type And Quantity:

2 uninsulated wire lead

## NSN 5910-01-365-9920

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0