## NSN 5910-01-365-9925

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-365-9925

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
7.4 millimeters
Body Width:
8.7 millimeters
Body Height:
3.7 millimeters
Terminal Diameter:
0.61 millimeters
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.056 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
40.0 ac-rms single section and 63.0 dc single section
40.0 ac-rms single section and 63.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
· ·
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene  Terminal Type And Quantity:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene  Terminal Type And Quantity: 2 uninsulated wire lead
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Plastic  Dissipation Factor At Reference Tempurature In Percent: 0.005  Terminal Surface Treatment: Solder  Dielectric Material: Plastic polypropylene  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a

No

## NSN 5910-01-365-9925

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0